



TECHNICAL SPECIFICATION

GEE COAT BONDING AGENT (BA-3)

DESCRIPTION:

GEE COAT BA-3 is An Acrylic polymer based product which is used in mortar and concrete as an admixture and bonding agent to increase its water resistance and durability.

SPECIAL CHARACTERISTICS:

Enhances the flexural and tensile strength of the mortar and render
Improves the chemical and abrasion resistant properties of the mortar
Reduces the water/cement ratio
Compatible with all types of cement
Excellent adhesion to most building materials
Similar thermal expansion and modulus properties like concrete
Provides good resistance to water and moisture vapor transmission
Can be applied in thin screed without cracking
Easy to use
Reduces shrinkage
Good resistance to salt protection
Can be used in potable water applications

CLEAN UP:

Use clean fresh water for cleaning brushes and equipment before product dries up. Dry product may be removed with not soapy water or detergent solvents such as chlorinated (Non Flammable) solvent or mineral spirit (Flammable)



FOR INDUSTRIAL USE ONLY:

Keep Out of the reach of Children

The information and specification given herein is true, correct and reliable but is given only for the guidance of the customers. We guarantee the quality of the product but cannot guarantee the result as product often used under conditions beyond our control. Users are advised to confirm the suitability of the product by necessary prior tests which alone can ensure that the product is suitable for a specific application. Our warranty is limited to the replacement of defective product.

