



MATERIAL SAFETY DATA SHEET

CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

COMPANY INFORMATION:

GREEN LAND ADHESIVE MATERIALS MANUFACTURING L.L.C
P.O. Box: 2187, Ajman Jurf Industrial Area-2
Ajman, United Arab Emirates
Email: info@greenlandadhesive.ae

PRODUCT INFORMATION:

PRODUCT NUMBER	:	GL MRA-3
PRODUCT NAME	:	GEE COAT MRA-3
PRODUCT DESCRIPTION	:	MOULD RELEASING AGENT

RECOMENDED USE:

Applied to moulds or forms into which a concrete mix is poured. Specialized grade developed to meet requirements of concrete pipe manufacturers using the centrifugal casting process.

HAZARDS IDENTIFICATION

Product is classified as hazardous according to Schedules 1 to 6 of the Hazardous Substances (Minimum Degrees of Hazard) Regulations 2001 of the HSNO Act, 1996.

HSNO Classifications: 3.1C, 6.1E, 6.3B, 6.5B, 9.1B

Signal word: WARNING

HAZARD STAYTMENTS:

H226 Flammable liquid and vapour
H303 May be harmful if swallowed
H305 May be harmful if swallowed and enters airways
H316 Causes mild skin irritation
H317 May cause an allergic skin reaction
H411 Toxic to aquatic life with long-lasting effects.



PREVENTION STAYTMENTS:

- P102 Keep out of reach of children.
P103 Read label before use.
P210 Keep away from heat, open flames, hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond containers and receiving equipment.
P241 Use explosion proof electrical/ventilating/lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P261 Avoid breathing vapours
P272 Contaminated work clothing should not be allowed out of the workplace
P273 Avoid release to environment.
P280 Wear protective gloves and eye protection.

COMPOSITION : INFORMATION ON INGREDIANTS

Naphtha (petroleum), light aromatic	64742-96-6	10 - 30
Naphtha (petroleum), medium aliphatic	64742-88-7	30 – 60
Rosin (colophony)	8050-09-7	5 – 15
Fish oil	8016-13-5	< 5

FIRST AID MEASURES

For advice, contact National Poison Centre (0800 POISON ; 0800 764 766) or a doctor. Have product container or label available.

SWALLOWED:

If swallowed, do NOT induce vomiting. Rinse mouth. Give a glass of water to drink slowly if person is conscious. Avoid giving ilk, oils or alcohol. Never give liquid to person showing signs of drowsiness or if unconscious. Where there is a risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Begin artificial respiration if victim is not breathing. Use mouth to nose rather than mouth to mouth. Get medical attention.

SKIN CONTACT:

If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. If irritation persists get medical attention.

EYE CONTACT:

Hold eyelids apart and flush the eye continuously with running water. Continue flushing for at least 15 minutes. Remove contact lenses if present and easy to do, after the first 5 minutes and continue rinsing. Get medical attention if irritation persists.



INHALATION:

Move the victim to fresh air immediately. Keep warm and at rest until recovered. Get medical attention if recovery is not rapid.

First Aid Facilities: Provide eye bath and hand washing facilities.

Advice to Doctor: Treat according to symptoms. Risk of aspiration into lungs with potential to cause chemical pneumonitis.

FIRE FIGHTING MEASURES

Flashpoint	:	40°C
Flammable limit	:	LFL : - UFL: -
Extinguishing media	:	Foam, CO2 or dry chemical. Use water spray or water fog on large fires only.
Fire & Explosion hazards:		Flammable liquid and vapour. The vapour forms explosive mixtures with air. Do not breathe smoke, gases or vapours generated in a fire. Decomposition products may be toxic.
Firefighting Equipment:		Full protective clothing and self-contained breathing apparatus (SCBA).

IN EVENT OF FIRE:

- Alert Fire Bridge (111); advise location and nature of hazard.
- Keep bystanders away.
- Wear breathing apparatus and protective gloves.
- Shut off product that may „fuel“ a fire if safe to do so.
- Eliminate sources of ignition
- If safe, switch off electrical equipment until vapour hazard removed.
- Use fine water spray to control fire and cool adjacent area.
- Allow trained personnel to attend a fire in progress, providing fire-fighters with this Safety Data Sheet.
- Prevent product and extinguishing media from escaping to drains and waterways.



HAZARDDDS FROM COMBOSITION PRODUCTS:

Product will emit toxic fumes of carbon monoxide, carbon dioxide, nitrogen oxides, smoke..

Hazchem Code : 3Y

ACCIDENTAL RELEASE MEASURES

Emergency Procedures & Containment:

Refer to "Fire Fighting Measures", "First Aid Measures" and "Stability and Reactivity".

MINOR SPILLS:

- Clean up spills immediately.
- Remove all ignition sources.
- Avoid breathing vapours and contact with skin and eyes.
- Wear personal protective equipment.
- Contain and absorb small quantifies with vermiculite or other absorbent material.
- Collect residues and waste material in a labeled container.
- Seal container and dispose of safely.

MAJOR SPILLS:

- Clear area of personnel and move upwind.
- Alert Fire Bridge (111); advise location and nature of hazard.
- Wear breathing apparatus plus protective gloves.
- Eliminate ignition sources, naked lights. No smoking.
- Stop leak if safe to do so.
- Water spray or water fog may be used to disperse or absorb vapour.
- Contain spill with sand, earth or vermiculite.
- Use spark-free shovels and explosion proof equipment.
- Prevent by any means available, spillage from entering drains, sewers, watercourses, or lowlying areas.
- Increase ventilation.
- Collect recoverable product into labeled contains for recycling.
- Absorb remaining product with sand, earth or vermiculite.
- Collect solid residues and seal in labelled drums for disposal.
- Wash area and prevent run off into drains.
- If contamination of drains or waterways occurs, advise Emergency Services and Local or Regional authority.



HANDLING AND STORAGE

PRECAUTION FOR SAFE HANDLING:

Flammable liquid and vapour. Read product label before use. Use in well-ventilated area. Avoid smoking, naked lights or ignition sources. Avoid generation of static electricity. Do NOT use plastic buckets. Use only spark-free tools.. Avoid all personal contact including by inhalation. Wear personal protective equipment and clothing including gloves and wash hands with soap and water after handling.

CONDITIONS FOR SAFE STORAGE:

Store in original packaging in a cool, dry well-ventilated place out of reach of children. Check containers periodically for leaks or distortion.

INCOMPATIBLE MATERIALS:

Oxidizing agents and chlorine products.

EXPOSURE CONTROLS : PERSONAL PROTECTION

HEALTH EXPOSURE STANDARDS:

A Workplace Exposure Standard (WES) has been set by the Occupational Safety and Health Service, NZ Department of Labour for a similar product and a component in this product.

WES-TWA	WES-STEL	
Naphtha (petroleum), light aromatic	25 – 100 ppm (125 mg/m3)	-
Naphtha (petroleum), medium aliphatic	300 ppm	

Biological limit values : None established

ENGINEERING CONTROLS:

Ventilation: Avoid breathing vapours. Use product outdoors or in well-ventilated area. Wear a SAA approved respirator when using in confined area or where over-exposure risk exists. Provide mechanical ventilation in confined areas. Use explosion-proof ventilation equipment.

PERSONAL PROTECTIVE EQUIPMENT:

Respiratory Protection: Where air concentration may exceed Workplace Exposure Standard, wear SAA approved respiratory protection. A half-filter mask and type „A“ filter material should be suitable.

Eye Protection: Protect eyes from splashes. Always use safety glasses with side shields, or wear goggles. Do not wear contact lenses.

Skin/ Body Protection: Wear chemical resistant gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. rubber, and clothing with long sleeves and long trousers or coveralls.

**PHYSICAL AND CHEMICAL PROPERTIES**

Appearance	-	Clear yellow
Odor	-	liquid
Flash Point	-	Solvent
Specific gravity @ 20 °C	g/ml	40 °C
Vapour Pressure @ 20 °C	mm Hg	0.76 – 0.84
Vapour Density @ 20 °C	kPa	Not available
Explosive Limits in Air	%	>1
Viscosity	cSt	Not available
Volatiles	%vol/vol	Not available
Alkalinity/acidity (as pH)	-	100
Solubility in Water	% w/w	Not applicable
		Immiscible

The values listed are indicative of this product's physical and chemical properties.

STABILITY AND REACTIVITY

Chemical Stability	:	Stable at room temperature and pressure.
Conditions to avoid	:	Sources of heat, ignition, open flames and contact with oxidizing agents, chlorine bleaches, pool chlorine.
Hazardous decomposition products	:	No decomposition products except on burning. See "Fire Fighting Measures" and "Hazardous Reactions".
Hazardous reactions	:	With oxidizing agents.



TOXICOLOGICAL INFORMATION

INJECTION:

Swallowing small amounts or from vomiting may cause aspiration into lungs and cause chemical pneumonitis or pulmonary odema. If swallowed, symptoms may include gastrointestinal upsets headaches, nausea, dizziness and tracheal burning.

EYE CONTACT:

This product may be irritating to the eyes resulting in tearing and redness but will not permanently damage eye tissue.

SKIN CONTACT:

This product can be mildly irritating to the skin. Prolonged or repeated exposure may defat skin leading to drying, cracking and possibly contact dermatitis.

INHALATION:

Vapours may cause discomfort to the upper respiratory tract. Symptoms of over-exposure may be drowsiness, dizziness, nausea, headaches and other central nervous system effects.

CHLORIC EFFECTS:

Repeated or prolonged exposure to mixed hydrocarbons may result in dizziness, weakness, irritability, lack of concentration and memory loss, tremor of extremities, e.g. fingers, weight loss, anemia, ill-effects to liver and kidneys.

Other Health Effects Information : None

Toxicological Information : None

ECOLOGICAL INFORMATION

ECOTOXICITY:

Aquatic toxicity	:	This product has been classified as being toxic to aquatic life. Do not discharge product to sewer, drains or waterways.
Persistence/degradability	:	Not expected to be persistent or bioaccumulative.
Mobility	:	Product will float on water. Its highly volatile and will rapidly evaporate.
Other information	:	Not available.

ENVIRONMENTAL EXPOSURE STANDARDS:

EEL (WATER)	:	Not set
EEL (SOIL)	:	Not set
EEL (SEDIMENTS)	:	Not set



DISPOSAL CONSIDERATIONS

DISPOSAL METHODS:

Empty packaging should be taken for recycling, recovery or disposal through a suitably qualified or licensed contractor. Care should be taken to ensure compliance with national, regional and local authority regulations. Packaging may still contain product vapours.

TRANSPORT INFORMATION

UN Number : 1993
Shipping name : FLAMMABLE LIQUID, N.O.S. (contains petroleum naphtha)
Class: 3 packing group: III
Hazchem code : 3Y

Dangerous Goods Segregation

his product is classified as Dangerous Good Class 3.

Please consult NZS 5433:2007 Transport of Dangerous Goods on Land for information.

OTHER INFORMATION

ABBREVIATIONS:

CAS No : Chemical Abstracts Number
ERMA : Environmental Risk Management Authority
HSNO : Hazardous Substances and New Organisms
NZCI : New Zealand Chemical Inventory
STEL : Short Term Exposure Limit
TWA : Time Weighted Average
WES : Workplace Exposure Standard

References : Supplier Material Safety Data Sheets

ERMA website: www.ermanz.govt.nz

The information sourced for the preparation of this document was correct and complete at the time of writing to the best of the writer's knowledge. The document represents the commitment to the company's responsibilities surrounding the supply of this product, undertaken in good faith. This document should be taken as a safety guide for the product and its recommended uses, but is in no way an absolute authority. Please consult the relevant legislation and regulations governing the use and storage of this type of product. For further information, please contact **Green Land Adhesive Materials Manufacturing L.L.C.**